



AQUA PURE PROFESSIONAL

TECHINICAL DATA SHEET

Specification	Aqua Pure Professional
Procedure	Vaporizing fog machine with water
Total requirement	3.4 kW
Power of heater	2.2 kW
Voltage	220–245 V (208–245 V) / 50 Hz (60 Hz)
Phase	1
Warm-up time	10 min
Fluid consumption @ 100%	200 ml/min
Fluid consumption @ 30%	60 ml/min
Fog volume	175 m ³ /min (6500 CFM)
Water consumption	1–24 L/hr
Tube diameter	150 mm
Tube length (horizontal)	Max. 40 m
Tube length (vertical)	Up to 20 m (67 ft)
Fluid tank capacity	5 L
Water tank capacity	5 L (optional 25 L)
Fog output adjustable	0–100%
Continuous fogging	<60%
Coverage per minute	Up to 300 m ²
Control	DMX 512 / RDM
Temperature control	Microprocessor
Overheating protection	Heater block / thermostatPump / thermal switch



AQUA PURE ELITE

TECHINICAL DATA SHEET

Specification	Aqua Pure Elite
Procedure	Vaporizing fog machine with water
Total requirement	4.8 kW
Power of heater	2.2 kW
Voltage	220–245 V (208–245 V) / 50 Hz (60 Hz)
Phase	2
Warm-up time	10 min
Fluid consumption @ 100%	200 ml/min
Fluid consumption @ 30%	60 ml/min
Fog volume	225 m ³ /min (8400 CFM)
Water consumption	1–48 L/hr
Tube diameter	150 mm
Tube length (horizontal)	Max. 40 m
Tube length (vertical)	Up to 20 m (67 ft)
Fluid tank capacity	5 L
Water tank capacity	10 L (optional 25 L)
Fog output adjustable	0–100%
Continuous fogging	<60%
Coverage per minute	Up to 400 m ²
Control	DMX 512 / RDM
Temperature control	Microprocessor
Overheating protection	Heater block / thermostatPump / thermal switch